

Case Study




MICROFINISH VALVES

Quality you can trust.

Microfinish ESD's for critical applications in a refinery

Microfinish Valves Pvt Ltd. recently supplied several Emergency Shutdown (ESD) systems to Indian Oil Corporation Ltd. for Booster & tail gas compressors. The ESD's were 4" (DN 100), 6" (DN 150) & 8" (DN 200) sizes, class 300, full port, trunnion mounted ball valves with 10" extended bonnet for fire proofing of actuator and accessories. The complete automated packages included a scotch-yoke spring return actuator, Solenoid Valve, Air Filter Regulator, Limit Switches, Positioner and Air Lock Relay, as well as, an integral 100 litre stainless steel compressed air accumulator assembled with Non Return Valve, Pressure Relief Valve, Pressure Gauge and Pressure Switch.

The automation package was equipped with a fire proof jacket, allowing the ESD to function properly at temperatures as high as 1000°C for a duration of 30 minutes.

The complete ESD systems were redesigned, assembled and meticulously tested at Microfinish Valves Pvt Ltd facility. In the event of a main header air failure, the ESD is designed to remain in the last position, preventing a dangerous unintentional operation. The air accumulator is sized to allow two fully open/close cycles in case the system is disconnected from the main header.

As per site safety specifications the ESD systems are designed to shut-off the line in less than 1 second. This is a critical factor because the refinery is subject to a major safety issue in the event the ESD does not operate in this time frame. System reliability is an essential element of the ESDs as they will stay in their armed position most of their life time and only in the case of an emergency must stroke the valve rapidly to its closed position. To ensure that valve moves to the fail safe position on demand, a Positioner is provided which can be programmed to do the Partial Stroke testing (PST) in predefined intervals. Based on the results of PST, the health of the valve can be assessed and remedial actions can be initiated. The ESD's are certified to work in a SIL 3 loop which means that for low demand operation the Probability of Failure on Demand (PFD) should be between 0.001-0.0001, in other words, as a minimum, out of 1,000 demands for immediate closing 999 events will end up successfully.

These distinctive ESD systems are another solution from Microfinish valves and our desire to enhance the reliability and safety in the refining industry.



8" IDN ZOOI ESD after calibration and testing

- Fire proof jacket allows safe operation for 30 min. at 1000°C
- Rapid closing time in less than 1 sec.
- 100 litre integral compressed air tank. avoids dangerous unintentional operation
- Partial Stroke Test (PST) device included for system reliability check
- Fire safe certified to API 607 and ISO 10497
- Certified to work in a SIL 3 loop

The automation package was equipped with a fire proofjacket, allowing the ESD to function properly at temperatures as high as 1000°C for a duration of 30 minutes

The complete ESD systems were designed, assembled and meticulously tested at Microfinish valves facility. In the event of a main header air failure, the ESD is designed to remain in the last position, preventing a dangerous unintentional operations The air accumulator is sized to allow two fully open/close cycles in case the system is disconnected from the main headers

These distinctive ESD systems are another solution from Microfinish valves and our desire to enhance the reliability and safety in the refining industry.



8" (DNZOO) ESD with fire proof jacket



MICROFINISH VALVES

Quality you can trust.

India

Microfinish Valves Pvt. Ltd.

B 161-162, Industrial Estate, Gokul Road,
Hubballi - 580030, Karnataka, India.

Tel: 91.836.2212404

Fax: 91.836.2331438

sales@microfinishgroup.com

www.microfinishgroup.com

Americas

Microfinish Valves, Inc.

7807 Bluff Point Drive, Suite 190
Houston, Texas 77086

Tel: 281.885.4250

Fax: 281.866.0996

sales@microfinishvalvesinc.com

www.microfinishvalvesinc.com